

What is claimed is:

1. A device for storing data, comprising:

an interfacing circuit that includes a data communication path through which said data can be bilaterally communicated between said device and an external device, which is coupled to said device with an interface cable, and a power-supplying path through which a power current can be bilaterally supplied between said device and said external device, wherein said interface cable also includes said data communication path and said power-supplying path;

a data-storing unit to store said data sent from said interfacing circuit; and

a plurality of interface connecting ports serving as input/output terminals of said interfacing circuit, wherein said interface cable can be connected to one of said interface connecting ports.

2. The device of claim 1,

wherein said external device is a personal computer and said data-storing unit is a magneto-optics disk drive, and a peripheral device can be also coupled to said device through another one of said interface connecting ports with another interface cable.

BOOKS FOR SALE

BOOKS FOR SALE

BOOKS FOR SALE

BOOKS FOR SALE

[illegible][illegible][illegible]

another one of said interface connecting ports with a second interface cable.

5. The device of claim 4,

wherein a second power current, being a part of said first power current outputted by said power-supply section, is also supplied to said peripheral device through said power-supplying path included in said second interface cable connected to said second interface connecting port.

6. The device of claim 5,

wherein said external device is a personal computer and said data-storing unit is a magneto-optics disk drive.

7. The device of claim 5, further comprising:

a power controller to control an amount of said second power current to be supplied to said peripheral device.

8. The device of claim 5, further comprising:

a power controller to control said interfacing circuit in such a manner that a third power current, supplied from said external device through said first interface connecting port, is further supplied to said peripheral device through said second interface connecting port, only when said power

TOP SECRET 4498660

[illegible][illegible]

BOOKS FOR SALE

BOOKS FOR SALE

BOOKS FOR SALE

BOOKS

BOOKS FOR SALE

another power current, supplied from said power-supply unit, among said peripheral devices coupled through said interface connecting ports other than said first interface connecting port.

12. The device of claim 9,

wherein said external device is a personal computer and said data-storing unit is a magneto-optics disk drive.

13. The device of claim 9,

wherein said power controller is driven by a power current supplied from said external device through said first interface connecting port.

14. The device of claim 9,

wherein said power controller is driven by a power current supplied from said power-supply section when said power-supply section is activated, while said power controller is driven by a power current supplied from said external device through said first interface connecting port when said power-supply section is deactivated.

09985644-110904